



TECHNICAL SHEET

VERTICAL TRAILED **COMMANDER**

EN

It brings to the attention of all potential customers, all recipients, and to the maximum extent possible, external interlocutors, that Faresin Industries S.p.A. adopts a general Disclaimer regarding the description of the technical and functional characteristics of its machineries, as well as the manner of their use, also with regard to their safety. The Disclaimer must be understood as having a general scope, and therefore Faresin Industries s.p.a. invites to know it, also by accessing the website: www.faresindustries.com



Models		2.30	2.40
Dimensions			
[A] Total length	mm	8294	8780
[B] Height	mm	3540	3920
[C] Width	mm	2900	2900
[D] Outside wheels	mm	2385	2385
[E] Unloading height	mm	711	711
[F] Drawbar axle length	mm	4775	4775
Transmission			
Mechanical transmission		●	●
Required power	kW/hp	96-130	140-190
Power take-off	rpm	1000	1000
Weights			
Capacity	m ³	30	40
Unladen weight	kg	12501	14002
Maximum capacity	kg	12002	15998
Mixing tub			
Augers	n.	2	2
2-speed gearbox		●	●
Load sensors	n.	6	6
Tank thickness	mm	8	8
Tank bottom thickness	mm	25	25
thickness spiral	mm	22	22
Auger diameter	m	2.3	2.5
Number of auger spiral revolutions		3	3.5
Planetary auger reducer	rpm	36@1000	36@1000
Number of knives		11+11	13+13
Stainless steel tank coating		○	○
Manual counter-knives	n.	2	2
Hydraulic counter-knives		○	○
Mechanical / Electric distributor		○	○
Chassis		●	●
Containment ring		-	-
Standard discharge		Sides with fixed direct chute - Direct rear	Sides with fixed direct chute - Direct rear
Axles			
Double axle with balance		●	●
Brakes			
Braking system		○	○
Negative hydraulic / pneumatic / parking brakes		○	○
Other			
Standard tyres		255/70 R22.5	255/70 R22.5

● Standard

○ Optional

- Not available

